

RADC-TR-72-239
Final Technical Report
August 1972



INVESTIGATION OF 10.6 MICRON PROPAGATION PHENOMENA
(2880-8)

AD 749504

The Ohio State University

ElectroScience Laboratory

Department of Electrical Engineering
Columbus, Ohio 43212

Sponsored by
Defense Advanced Research Projects Agency
ARPA Order No. 1279

Approved for public release;
distribution unlimited.

The views and conclusions contained in this document are those
of the authors and should not be interpreted as necessarily
representing the official policies, either expressed or implied,
of the Defense Advanced Research Projects Agency or the U. S.
Government.

Reproduced by
**NATIONAL TECHNICAL
INFORMATION SERVICE**
U.S. Department of Commerce
Springfield VA 22151

Rome Air Development Center
Air Force Systems Command
Griffiss Air Force Base, New York

D D C
R E P R I V E
OCT 11 1972

B

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)

The Ohio State University ElectroScience Laboratory,
Department of Electrical Engineering, Columbus, Ohio2a. REPORT SECURITY CLASSIFICATION
Unclassified
2a. GROUP

3. REPORT TITLE

INVESTIGATION OF 10.6 MICRON PROPAGATION PHENOMENA

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Final Technical Report - 8 April to 8 July 1972

5. AUTHOR(S) (Last name, first name, initial)

Damon, Edward K.

6. REPORT DATE

August 1972

7a. TOTAL NO. OF PAGES

6

7b. NO. OF REFS
3

8a. CONTRACT OR GRANT NO.

Contract No. F30602-70-C-0003

9a. ORIGINATOR'S REPORT NUMBER(S)

b. ARPA Order No. 1279

ElectroScience Laboratory 2880-8

c. Program Code No. 9E20

9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)

d.

RADC-TR-72-239

10. AVAILABILITY/LIMITATION NOTICES

Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES Monitored by

Raymond P. Urtz, Jr.
RADC (OCSE), GAFB, NY 13440

12. SPONSORING MILITARY ACTIVITY

Advanced Research Projects Agency
Arlington, VA 22209

13. ABSTRACT

This report summarizes the technical details of work performed at The Ohio State University ElectroScience Laboratory during the period 9 April, 1972 to 8 July, 1972.

The computer interface to the OSU data processing facility has been completed so that the output of the infrared scanner system installed at RADC can now be analyzed. Appropriate software has been written and tested for image reconstruction. With this step, the complete system is now operational.

1a

UNCLASSIFIED

Security Classification

14.

KEY WORDS

LINK A

LINK B

LINK C

ROLE

WT

ROLE

WT

ROLE

WT

10.6 microns
 Atmospheric imaging
 Image restoration
 Computer interface

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

18
UNCLASSIFIED

Security Classification

INVESTIGATION OF 10.6 MICRON PROPAGATION PHENOMENA

Edward K. Damon

Contractor: The Ohio State University
ElectroScience Laboratory
Contract Number: F30602-70-C-0003
Effective Date of Contract: 8 July 1969
Contract Expiration Date: 8 July 1972
Amount of Contract: \$349,943.00
Program Code Number: 9E20

Principal Investigator: Dr. William G. Swarner
Phone: 614 422-6677

Project Engineer: Raymond P. Urtz, Jr.
Phone: 315 330-3443

Approved for public release;
distribution unlimited.

This research was supported by the
Defense Advanced Research Projects
Agency of the Department of Defense
and was monitored by Raymond P. Urtz,
Jr., RADC (OCSE), GAFB, NY 13440 under
Contract F30602-70-C-0003.

1C

PUBLICATION REVIEW

This technical report has been reviewed and is approved.

Raymond P. Ulrich
RADD Project Engineer

ABSTRACT

This report summarizes the technical details of work performed at The Ohio State University ElectroScience Laboratory during the period 9 April, 1972 to 8 July, 1972.

The computer interface to the OSU data processing facility has been completed so that the output of the infrared scanner system installed at RADC can now be analyzed. Appropriate software has been written and tested for image reconstruction. With this step, the complete system is now operational.

CONTENTS

	Page
I. INTRODUCTION	1
II. DATA HANDLING	1
III. IMAGE RESTORATION	3
IV. SUMMARY	4
REFERENCES	6

I. INTRODUCTION

This is the eighth technical report on Contract No. F30602-70-C-0003 entitled "Investigation of 10.6 Micron Propagation Phenomena." This report covers the period 9 April 1972 to 8 July 1972.

→ This program initially provided theoretical backup information to the RADC Atmospheric Optical Propagation Studies Program and is currently centered on the study of atmospheric imaging and the restoration of atmospherically degraded 10.6 micron images. The general aim is to provide initial attempts at image restoration, to determine potential problems, and to obtain data useful for preliminary systems design. For this purpose, a system has been completed, tested and delivered to RADC which will simultaneously sample with 40 x 40 resolution two 10.6 micron images at 200 frames per second and record these images in digital format on magnetic tape.

→ Primary effort during the past quarter has been devoted to completing and testing the hardware and software for decoding the special Miller Code tapes from the scanner system and interfacing this hardware with the data processing facility at The Ohio State University ElectroScience Laboratory. Test tapes recorded at RADC have been successfully converted to standard digital tapes and the images restored using the OSU FFT software.

II. DATA HANDLING

Installation of the interface between the modified Datacraft DC 6024-3 Data and Signal Processing System and the decoded output of the serial digital (Miller Code) recorder has been completed and the necessary assembly language software has been written that will generate the signals required by both the computer and the interface logic to transfer data into the computer. This interface gives the ElectroScience Laboratory Data Reduction Facility the capability of generating DC 6024-3 compatible tape to serve as bulk storage of input data for the existing image restoration software.

The signals that must be transmitted between the DC 6024-3 and the interface in order to transfer a 24 bit word, supplied by the OSU playback system, into the computer have been discussed in a previous report. This section contains a description of the software required to transfer blocks of 1600 words, via an Automatic Block Controller (ABC), into the computer memory and then to generate a computer compatible tape containing this data. The ABC transfer feature allows a block of data (in our case 1600 words) to be transferred, without program intervention, between memory and a specified peripheral unit. Further, once the software program has initiated an ABC transfer over a given channel, the program can continue execution provided that subsequent program operations do not involve the channel on which the ABC transfer was initiated until

the transfer is completed. As will be seen later, this feature allows data to be read from the interface (Channel 3) while writing a previously stored block of data from memory onto the disc (Channel 5).

Figure 1 indicates the word format available from the interface unit.¹ Using this format, a frame from each channel and the associated code bits are packed into a single block of 1600 computer words. The interface unit has two image selector switches (CH 1 and CH 2) capable of gating either the A or B image, as scanned by the ElectroScience Laboratory Dual Channel Infrared Image Scanner,² to either or both channels. For the purposes of this report we will always assume Channel 1 carries image A while Channel 2 carries image B.




Fig. 1. Word format.

Because of the continuous rate at which data is being transmitted to the interface by the Miller Code decoder (12.5 Blocks or Frames/Sec or 20.8 K words/sec), data can not be written directly on the present computer tape units, which have a maximum writing rate of 12 K words/sec, without skipping every other frame. Thus, the interface software reads data into memory then transfers it onto disc storage, which has a read write capability of a nominal 100 K words/sec. The disc then acts as intermediate storage for the data. The important feature of the disc is that one has control over the frequency at which blocks are read off disc. This allows blocks to be read at a reduced rate permitting them to be preprocessed by the DC 6024-3 prior to being written on computer tape.

After a block is retrieved from the disc, it is read, word by word, into the A register of the computer where by using logical ANDing and shifting operations it is split into the A image frame (CH 1 frame), the B image frame (CH 2 frame) and the code bits (CH 1 and CH 2) are removed. The frames are then recorded in series (CH 1, CH 2, CH 1, ... etc.) on computer tape.

The present available disc working storage will hold 2133 blocks of data or about 10.5 seconds of real time data (data recorded at 200 frames/sec in real time). This quantity of data fills one computer tape but represents only about 1% of the data recorded on a Miller Code tape. Hence, the Miller Code tape must be visually reviewed and sections of interest selected for conversion to computer tape and subsequent data analysis.

Figure 2 shows the flow of data from the time it is read into memory until the time when the two frames obtained from each block are written on tape. The key to flow is the ABC transfer which allows the computer to be reading data from the interface into a memory buffer while writing a previously filled buffer on disc.




Fig. 2. Image processing flow diagram.

III. IMAGE RESTORATION

The ElectroScience Laboratory image processing software has been tested and documented previously.³ However, the images processed at that time were obtained by digitizing filmed recordings of the images presented on the scanner display scope.³ Now, with the completion of the digital recording and playback portions of the image scanning system and the completion of the interface between the playback system and the DC 6024-3 computer the restoration data will be the actual data sampled by the scanning disc.

A flow diagram reviewing the image processing software is included in Fig. 3. As stated previously, the two images (A and B) are recorded serially on the computer tape. The image processing program sees the first image and all succeeding odd numbered images as possible candidates for the system point spread function (psf) array while the second and all succeeding even images are seen as possible candidates for the degraded image array.

At present, only tapes with one point source have been tested and hence only a single channel of the dual channel scanning capability is being used. The second channel of data will be available in the future, since the dual transmitting optics have now been delivered. Channel 2 containing B images is the data channel while Channel 1 contains only system noise. Only slight software modifications are required to handle the single channel of data. First, the tape generated by the interface software will contain only Channel 2 (B images) recorded on it and secondly the first B image and all the succeeding odd images will be candidates for the psf while the second B image and all succeeding even images will be candidates for the degraded image in the restoration program.

IV. SUMMARY

All components and documentation for an imaging system for 10.6 microns have now been delivered and installed at the RADC PATS site. These include a dual channel infrared image scanner, digitizer, and serial digital (Miller Code) recorder for the receiving system. The transmitting system provides two point sources with adjustable separation and simultaneously transmits both 10.6 micron and 0.63 micron wavelengths.

Specialized equipment has been constructed, tested, and interfaced with a data processing facility at the ElectroScience Laboratory to read the Miller Code tapes and to analyze and restore the images. Fast Fourier Transform image restoration software has been written and tested.

The complete system is particularly capable of measurements of isoplanatic patch size and atmospheric optical transfer function in the infrared, where very little such information is now available to assist the designer of imaging or tracking systems which must operate in the turbulent atmosphere.




Fig. 3. Basic computer program for image restoration.

REFERENCES

1. "Investigation of 10.6 Micron Propagation Phenomena," Report 2880-7, June 1972, The Ohio State University ElectroScience Laboratory; prepared under Contract F30602-70-C-0003 for Rome Air Development Center. (RADC-TR-72-158).
2. "Investigation of 10.6 Micron Propagation Phenomena," Report 2880-6, March 1972, The Ohio State University ElectroScience Laboratory; prepared under Contract F30602-70-C-0003 for Rome Air Development Center. (RADC-TR-72-157).
3. "Investigation of 10.6 Micron Propagation Phenomena," Report 2880-4, August 1971, The Ohio State University ElectroScience Laboratory; prepared under Contract F30602-70-C-0003 for Rome Air Development Center. (RADC-TR-71-202).

ACCESSION #	
NTIS	White Section <input checked="" type="checkbox"/>
D C	Diff. Section <input type="checkbox"/>
UNA	<input type="checkbox"/>
JUSTIFICATION
BY	
DISTRIBUTION/AVAILABILITY CODES	
DATA	A, AIL, and/or SPECIAL
A	

If this copy is not needed, return to RADC (OCSE), GAFB, NY 13440.